



PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>7</sup> :

B60R 1/06

A1

(11) International Publication Number:

WO 00/69683

(43) International Publication Date: 23 November 2000 (23.11.00)

(21) International Application Number: PCT/NL00/00326

(22) International Filing Date: 17 May 2000 (17.05.00)

(30) Priority Data:

1012090

18 May 1999 (18.05.99)

NL

(71) Applicant (for all designated States except US): IKU HOLD-  
ING MONTFOORT B.V. [NL/NL]; Waardsedijk Oost 9,  
NL-3417 XJ Montfoort (NL).

(72) Inventor; and

(75) Inventor/Applicant (for US only): BROUWER, Stefan, Frits  
[NL/NL]; Hollanderstraat 22, NL-2517 HK The Hague  
(NL).(74) Agent: PRINS, A., W.; Vereenigde, Nieuwe Parklaan 97,  
NL-2587 BN The Hague (NL).(81) Designated States: AE, AG, AL, AM, AT, AU, AZ, BA, BB,  
BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM,  
DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL,  
IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU,  
LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT,  
RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ,  
UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH,  
GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian  
patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European  
patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR,  
IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF,  
CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published

With international search report.

(54) Title: MOVEMENT MECHANISM

(57) Abstract

A movement mechanism comprises a substantially spherical holder (1) and a substantially spherical bowl (2) which, one inserted into the other, are rotatable relative to each other about a first axis, the X-axis, and a second axis, the Y-axis, which axes lie in a plane substantially coinciding with the plane of the outer edge of the holder or extending parallel thereto. Between the holder and the bowl, a dish (5) is present, which is connected to the bowl for rotation about the X-axis only and connected to the holder for rotation about the Y-axis only. In a particular application, a mirror can be secured on the holder and drive means can be arranged in the holder for rotating the holder relative to the bowl, so that an adjustable wing mirror for a vehicle can be realized.

